

Wall Mount Switching Adapter SSA-0901 Single Output Series



www.seasonic.com



Applications:

- Mini ITX system
- POS
- DVR
- Printer
- Panel PC
- KIOSK
- LCD monitor
- Desktop Type

Features:

- Universal input
- Japanese Capacitor
- High efficiency 87%
- Meet CEC Level V, ErP Lot 7, Energy Star EPS 2.0
- Over voltage protection
- Over current protection
- Short circuit protection
- Over Thermal protection
- No load consumption $\leq 0.5W$

Output Specifications:

Model	Output power	Min. Load	Max. Load	Total power	Efficiency
SSA-0901-12	12V	0A	6.67A	80W	87%
SSA-0901-19	19V	0A	4.74A	90W	87%
SSA-0901-24	24V	0A	3.75A	90W	87%

General Specifications:

- Input voltage range: 90~264 Vac
- Input frequency: 47~63 Hz
- Input current: 2A (rms)
- Efficiency: $\geq 87%$ Average
- Leakage current: 3.5mA max.

Safety: CB, TUV, CCC, BSMI, CUL, CEC, KC, PSE, C-tick

EMC: CE, FCC,

Specification may change without prior notice

Dimension:

L139 × W58 × H33.3 mm
(L5.4 × W2.2 × H1.3 inch)

Sea Sonic Electronics Co., Ltd.
www.seasonic.com
sales@seasonic.com.tw
Tel: +886 2 2659 0338
Fax: +886 2 2659 0530

Seasonic Electronics Inc.
www.seasonicusa.com
usa@seasonic.com
Tel: +1 626 969 9966
Fax: +1 626 969 9986

Sea Sonic Europe B.V.
europe@seasonic.com
Tel: +31 (0)10-2262131
Fax: +31 (0)10-2519947

