

# DR Power Supply Series

24/48 VDC power supply for DIN-rail mounted products



## Features and Benefits

- 24/48 VDC power output
- Wide-range 40 to 120 W power wattage
- -10 to 60°C operating temperature ability

## Certifications



## Introduction

The DR Power Supply Series provides a reliable 24/48 VDC power source for industrial control systems. The Series has rugged, compact enclosures, and can operate reliably in temperatures between -10 and 60°C. The DR Power Supply Series has passed a 100% full load burn-in test and is UL/CUL listed, TÜV/CB certified, and CE marked.

## Specifications

### Output Power Parameters

Wattage	DR-4524: 48 W DR-75-24: 76.8 W DR-120-24: 120 W DR-75-48: 76.8 W DR-120-48: 120 W
Voltage	DR-4524: 24 VDC DR-75-24: 24 VDC DR-120-24: 24 VDC DR-75-48: 48 VDC DR-120-48: 48 VDC
Current Rating	DR-4524: 0 to 2 A DR-75-24: 0 to 3.2 A DR-120-24: 0 to 5 A DR-75-48: 0 to 1.6 A DR-120-48: 0 to 2.5 A
Ripple and Noise	DR-4524: 480 mVp-p DR-75-24: 150 mVp-p DR-120-24: 80 mVp-p DR-75-48: 240 mVp-p DR-120-48: 100 mVp-p
Voltage Adjustment Range	DR-4524: 21.6 to 26.4 VDC DR-75-24: 24 to 28 VDC DR-120-24: 24 to 28 VDC DR-75-48: 48 to 53 VDC DR-120-48: 48 to 53 VDC

Setup/Rise Time at Full Load	DR-75-48: 1000 ms, 60 ms at 230 VAC DR-75-24: 1800 ms, 60 ms at 115 VAC DR-120-48: 500 ms, 70 ms at 115 VAC DR-120-48: 500 ms, 70 ms at 230 VAC DR-120-24: 500 ms, 70 ms at 115 VAC DR-4524: 800 ms, 60 ms at 230 VAC DR-120-24: 500 ms, 70 ms at 230 VAC DR-75-48: 1800 ms, 60 ms at 115 VAC DR-75-24: 1000 ms, 60 ms at 230 VAC
Typical Hold Up Time at Full Load	DR-120-48: 32 ms at 115 VAC DR-75-48: 12 ms at 115 VAC DR-75-24: 12 ms at 115 VAC DR-120-24: 36 ms at 230 VAC DR-120-24: 32 ms at 115 VAC DR-4524: 60 ms at 230 VAC DR-120-48: 36 ms at 230 VAC DR-75-48: 60 ms at 230 VAC DR-75-24: 60 ms at 230 VAC

### Input Power Parameters

Voltage Range	DR-4524: 85 to 264 VAC (47 to 63 Hz) DR-75-24: 85 to 264 VAC (47 to 63 Hz) DR-120-24: 85 to 132 VAC (47 to 63 Hz) DR-75-48: 85 to 264 VAC (47 to 63 Hz) DR-120-48: 88 to 132 VAC (47 to 63 Hz) DR-120-24: 176 to 264 VAC (47 to 63 Hz) DR-120-48: 176 to 264 VAC (47 to 63 Hz) DR-4524: 120 to 370 VDC DR-75-24: 120 to 370 VDC DR-120-24: 248 to 370 VDC DR-75-48: 120 to 370 VDC DR-120-48: 248 to 370 VDC
Typical Efficiency	DR-4524: 80% DR-75-24: 80% DR-120-24: 84% DR-75-48: 81% DR-120-48: 85%
Typical Current	DR-4524: 0.75 A @ 230 VAC, 1.5 A @ 115 VAC DR-75-24: 0.96 A @ 230 VAC, 1.6 A @ 115 VAC DR-120-24: 1.6 A @ 230 VAC, 2.6 A @ 115 VAC DR-75-48: 0.96 A @ 230 VAC, 1.6 A @ 115 VAC DR-120-48: 1.6 A @ 230 VAC, 2.6 A @ 115 VAC
Inrush Current (cold start)	DR-4524: 56 A @ 230 VAC, 28 A @ 115 VAC DR-75-24: 40 A @ 230 VAC, 20 A @ 115 VAC DR-120-24: 40 A @ 230 VAC, 20 A @ 115 VAC DR-75-48: 40 A @ 230 VAC, 20 A @ 115 VAC DR-120-48: 40 A @ 230 VAC, 20 A @ 115 VAC

### Overload Protection

Rated Output Power	105 to 150%
Protection Type	Constant current limiting, recovers automatically after fault condition is removed

### Overvoltage Protection

Over-Voltage Range	DR-4524: 27.6 to 32.4 V DR-75-24: 29 to 33 V DR-120-24: 29 to 33 V DR-75-48: 58 to 65 V DR-120-48: 58 to 65 V
Protection Type	Shut down operating voltage, repower on to recover

## Physical Characteristics

Dimensions	DR-4524: 78 x 67 x 93 mm (3.07 x 2.64 x 3.66 in) DR-75-24: 55.5 x 100 x 125.2 mm (2.19 x 3.94 x 4.93 in) DR-120-24: 65.5 x 100 x 125.2 mm (2.56 x 3.94 x 4.93 in) DR-75-48: 55.5 x 100 x 125.2 mm (2.19 x 3.94 x 4.93 in) DR-120-48: 65.5 x 100 x 125.2 mm (2.56 x 3.94 x 4.93 in)
Weight	DR-4524: 400 g (0.88 lb) DR-75-24: 550 g (1.21 lb) DR-120-24: 650 g (1.43 lb) DR-75-48: 550 g (1.21 lb) DR-120-48: 650 g (1.43 lb)

## Environmental Limits

Operating Temperature	DR-4524: -10 to 50°C (14 to 122°F) DR-75-24: -10 to 60°C (14 to 140°F) DR-120-24: -10 to 60°C (14 to 140°F) DR-75-48: -10 to 60°C (14 to 140°F) DR-120-48: -10 to 60°C (14 to 140°F)
Max. Operating Temperature at Full Load	45°C
Ambient Relative Humidity	20 to 90% (non-condensing)

## Standards and Certifications

EMC	EN 50082-2, EN 55022 Class B, EN 61000-3-2 Class A, ENV 50204
Safety	EN 60950-1

## Warranty

Warranty Period	3 years
Details	See <a href="http://www.moxa.com/warranty">www.moxa.com/warranty</a>

## Package Contents

Device	1 x DR Power Supply Series power supply
Documentation	1 x warranty card

## Ordering Information

Model Name	Input Voltage	Output Voltage	Output Wattage	Operating Temp.
DR-4524	85 to 264 VAC 120 to 370 VDC	24 VDC	48 W	-10 to 50°C
DR-75-24	85 to 264 VAC 120 to 370 VDC	24 VDC	76.8 W	10 to 60°C
DR-120-24	88 to 132 VAC 176 to 264 VAC 248 to 370 VDC	24 VDC	120 W	10 to 60°C
DR-75-48	85 to 264 VAC (27 to 63 Hz) 120 to 370 VDC	48 VDC	76.8 W	-10 to 60°C
DR-120-48	88 to 132 VAC 176 to 264 VAC (47 to 63 Hz) by switch 248 to 370 VDC	48 VDC	120 W	-10 to 60°C

© Moxa Inc. All rights reserved. Updated Nov 12, 2018.

This document and any portion thereof may not be reproduced or used in any manner whatsoever without the express written permission of Moxa Inc. Product specifications subject to change without notice. Visit our website for the most up-to-date product information.