



OFT-10W01

10.1" Open Frame Tablet

- > Intel® Atom™ Processor Z3735F
- > 2GB RAM
- > 8GB or 32GB eMMC
- > PCAP Touch
- > 10/100 Ethernet (PXE Boot)
- > Touch board interface (Power/ Brightness/ Volume/ LED)
- > 16Bit programmable GPIO
- > RS232(TX/RX) or RS485
- > DC 12~24V Input
- > Optional Powered LAN 802.3AT (10" only)

+ Spec

System	
Processor	Intel® Atom™ Processor Z3735F 1.33GHz Quad Core CPU
System Memory	2GB DDR3L RAM
Storage	
Storage	8GB or 32GB eMMC
Panel	
LCD Size	10.1"
Resolution	1280x800
Luminance	350
Viewing angle	170° (H/V)
Touch Type	PCAP
I/O	
External I/O Connector	2 x USB 2.0 1 x micro USB Client(Android only) 1 x 10/100 Ethernet 1 x HDMI 1 x Head phone jack 1 x Micro SD slot 1 x DC jack
Internal I/O Connector	1 x 16 bit GPIO interface 1 x USB interface 1 x eDP & Dual channel 24bit LVDS 1 x backlight control & power 2 x speaker interface (1.2W stereo) 1 x A-MIC interface 1 x Touch Button connector 1 x DC input 4pin header 1 x I2C interface(optional) 1 x RS232(TX/RX) or RS485
Display	
Multiple Display	Windows/ Linux support extended mode; Android support clone mode only
Mechanical & Environmental	
Power Requirement	DC 12~24V Input
Power Type	DC Jack, DC input 4pin header (Optional Powered LAN 802.3AT)
Operating Temperature	0°C ~ 40°C
Storage Temperature	-10°C ~ 60°C0
Operating Humidity	0% ~ 90% Relative Humidity, Non-condensing
Weight	1.18kg
Dimension (L x W x H)	252 x 166 x 38mm
Certifications	
Certification Information	CE, FCC Class A
Software Support	
OS Information	Windows 10(32 bit)/ Android 4.4(64 bit) / Android 5.1(64 bit) / Ubuntu 16.04(64 bit)
Wireless Communication	
WLAN	802.11 b/g/n
Bluetooth	4.0



+ Ordering

OFT-10W01-8GB eMMC
(PN: OFT-10W01-7T39C-7R/9R)

OFT-10W01-32GB eMMC
(PN: OFT-10W01-7V37C-7R, OFT-10W01-7V38C-3R, OFT-10W01-7V39C-5R/8R)

OFT-10W01-32GB eMMC w/ Powered LAN
(PN: OFT-10W01-7V37C-2R, OFT-10W01-7V38C-4R, OFT-10W01-7V39C-2R/7R)

